


Product Datasheet


ECO HOUSTEN



Floodlight Luminaire

Description:

Suitable for surface mounting on somewhere. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Warranty	: 5 years	Kelvin	: 3000-4000-5000-6500
Lamp Type	: LED	CRI	: <90
Housing	: Aluminium	LED Lifetime	: 80.000 h
Optics	: Lens	Power Supply	: 110-240V 50-60Hz
Glass	: Tempered Glass	Op. Temp.	: -30°C / +50 °C
IP	: 66	Number Of LED	: 192

Prometrical Data:

Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
E-RFG1	100	Houston Rim Gear 1	12500	394-240-100
E-RFG2	120	Houston Rim Gear 2	15000	394-240-100
E-RFG3	140	Houston Rim Gear 3	17500	394-240-100
E-RFG4	150	Houston Rim Gear 4	18750	394-240-100

Technical Options:

*Dali

*Dimmer

Quality Certificate:


Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.