

Product Datasheet


HENDERSON



Downlight Luminaire

Description:

LED Downlights each offer different benefits from the beam distribution, trim selection and installation methods. Whether you are installing them in a new construction or in a retrofit application, they will fit seamlessly into your lighting application.

Technical Features:


Installation	: Surface	Kelvin	: 3000-4000-6000
Warranty	: 3 years	CRI	: >90
Lamp Type	: COB LED	LED Lifetime	: 80.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Reflector	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:

Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
HRG1	8	Henderson Ray Spot Gear 1	820	60-60-160
HRG2	20	Henderson Ray Spot Gear 2	2280	100-100-160

Technical Options:

*Dali

Colours


*Dimmer

*Emergency Kits

Quality Certificate:


Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.