


Product Datasheet

LOWLY



Pendant Luminaire



Description:

Suitable for pendant or surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Installation	: Surface - Pendant	Kelvin	: 3000-4000-5000-6500
Warranty	: 5 years	CRI	: >80
Lamp Type	: LED	LED Lifetime	: 50.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Optics	: Lens	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
LEG1	30	Lowly Pendant Gear 1	3840	345-193-367
LEG2	45	Lowly Pendant Gear 2	5760	345-193-367
LEG3	60	Lowly Pendant Gear 3	7680	345-193-367

Technical Options:

*Dali

*Dimmer

*Emergency Kits

Quality Certificate:



Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.enteckled.com.tr

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.