


Product Datasheet


ORANGE



Sterile LED Panel

Description:

Suitable for recessed mounting in unventilated or ventilated ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Installation	: Recessed	Kelvin	: 3000-4000-6500
Warranty	: 5 years	CRI	: >90
Lamp Type	: LED	LED Lifetime	: 50.000 h
Glass	: Difusser + Tempered glasses	Power Supply	: 110-240V 50-60Hz
IP	: 65	Op. Temp.	: -20°C / +45 °C

Prometrical Data:

Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
OPG1	14	Orange Sterile Panel Gear 1	1650	300-600-70
OPG2	30	Orange Sterile Panel Gear 2	3000	600-600-70
OPG3	38	Orange Sterile Panel Gear 3	3600	600-600-70

Technical Options:
Colours

*Dali

*Dimmer

*Emergency Kits

Quality Certificate:

Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.