

Product Datasheet
PAVO
Lineer Surface Luminaire
Description:

Suitable for suspended or surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Installation : Surface / Suspended

Warranty : 3 years

Lamp Type : LED

Housing : Aluminium

Glass : Difusser

IP : 40




Kelvin : 3000-4000-6000

CRI : >80

LED Lifetime : 80.000 h

Power Supply : 110-240V 50-60Hz

Op. Temp. : -20°C / +45 °C


Prometrical Data:

Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
PLG1	13	Pavo Lineer Surface Gear 1	1380	55-85-300
PLG2	19,5	Pavo Lineer Surface Gear 2	1820	55-85-600
PLG3	26	Pavo Lineer Surface Gear 3	2560	55-85-900

Technical Options:

*Dali

*Dimmer

*Emergency Kits

Colours

Quality Certificate:

CE

Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.