




Product Datasheet
SPEC RIM

Street Luminaire
Description:

Suitable for surface mounting on somewhere. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Warranty	: 5 years	Kelvin	: 3000-4000-5000-6500
Lamp Type	: LED	CRI	: <80
Housing	: Aluminium	LED Lifetime	: 100.000 h
Optics	: Lens	Power Supply	: 110-240V 50-60Hz
Glass	: Tempered Glass	Op. Temp.	: -30°C / +50 °C
IP	: 66	IK	: 09

Prometrical Data:

Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
SSL1-RIM	30	Spec Rim Gear 1	4200	560-240-100
SSL2-RIM	50	Spec Rim Gear 2	6150	560-240-100
SSL3-RIM	60	Spec Rim Gear 3	8610	560-240-100
SSL4-RIM	70	Spec Rim Gear 4	9850	560-240-100
SSL5-RIM	90	Spec Rim Gear 4	11860	560-240-100
SSL6-RIM	100	Spec Rim Gear 5	14200	560-240-100

Technical Options:

*Dali

*Dimmer

*Emergency Kits

Quality Certificate:

Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.edealight.com

EDEA LIGHT reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.